

## 10nM WHITE LIGHT NIGHT MODE

SAFE AREA IP66



# MARINE NAVIGATION AIDS

## 10nM WHITE LIGHT NIGHT MODE TECHNICAL SPECIFICATIONS

### KEY FEATURES

- Based on LED technology
- 10nM (nautical mile) night mode, white flashing (Morse Letter "U")
- Long life time >10 years life expectancy
- Low consumption
- Stabilised light output
- Lightweight and compact
- Low wind load factor
- Alarm/remote status control
- Easy to install
- No RF-radiations
- Light output alignment device
- Patented beacon ( EU 001929910-0001; Canada 145 189; USA D673,474)

### OPTICAL FEATURES

- Horizontal beam radiation 360°
- Vertical beam spread >2,5°
- PMMA lens

### OPTIONS

- Power supply AC or DC

### ELECTRICAL FEATURES

- Power supply for external control panel
- Average power consumption for night mode: 6W
- LED feeded at constant current
- Lightning protection inside controller

### MECHANICAL FEATURES

- Anodised aluminium body with heat-sink for natural draft air cooling
- RAL7035 painted aluminium body lamp
- Bottom wind collector for central heat-sink cooling
- Borosilicate glass cover protection
- Silicon gasket
- Degree of protection: IP66
- Operating temperature: -50°C to +80°C
- Storage temp. range: -20°C to +45°C
- Lamp unit weight: 6kg

### APPLY TO

- Offshore structures classified as safe areas
- Isolated wind turbine, beacon is located at not less than 6m and not more than 30m above Highest Astronomical Tide (HAT)
- Meteorological mast
- Other individual structure
- Used as main light to ensure that at least one light is visible upon approaching the structure from any direction

### INTERNATIONAL REGULATION


- Standard marking schedule for offshore installations, Decc 04/11
- CE marking

### PART NUMBER

- Part number:
  - ▶ **MNL-LXS-10nM-230VAC**
  - ▶ **MNL-LXS-10nM-24VDC**

# MARINE NAVIGATION AIDS

## 10nM WHITE LIGHT NIGHT MODE



### CERTIFICATIONS



### FEATURES



### TYPICAL APPLICATION

